

# PRODUCT CARD



PRODUCT CODE: OR-PRE-452/UNI  
EAN CODE: 5904988904938

## Time relay - activation for a preset time

Time relay - activation for a preset time



Case flammability standard  
**UL94:**

V0



Degree of protection (IP):

20

## General information

|  |                         |
|--|-------------------------|
| <b>Number and type of contacts:</b>                | 1P                      |
| <b>Contacts material:</b>                          | AgSnO2                  |
| <b>Rated load AC1:</b>                             | 16 A / 250 V AC         |
| <b>Rated load DC1:</b>                             | 16 A / 24 V DC          |
| <b>Maximum switching capacity in category AC1:</b> | 4000 VA                 |
| <b>Contact resistance:</b>                         | ≤ 100 mΩ                |
| <b>Maximum switching frequency:</b>                | 600 cykli/h             |
| <b>Nominal voltage:</b>                            | 230 V                   |
| <b>Operating voltage range:</b>                    | 0,9 - 1,1 Un            |
| <b>Oversvoltage category:</b>                      | III                     |
| <b>Case flammability standard UL94:</b>            | V0                      |
| <b>Switching life AC1:</b>                         | > 0,5 x 10 <sup>5</sup> |
| <b>Working temperature:</b>                        | -20°C~+50°C             |
| <b>Degree of protection (IP):</b>                  | 20                      |
| <b>Relative humidity:</b>                          | do 85%                  |
| <b>impact resistance:</b>                          | 15 g                    |
| <b>vibration resistance:</b>                       | 0,35 mm DA              |
| <b>Dimensions - depth:</b>                         | 90 mm                   |
| <b>Dimensions - width:</b>                         | 17,5 mm                 |
| <b>Dimensions - height:</b>                        | 64,5 mm                 |
| <b>Net weight:</b>                                 | 66 g                    |